WIND EXPOSURE & VELOCITY									
NOISE BARRIER TYPE	WIND EXPOSURE	WIND VELOCITY (MPH)							
18A	B1	80							
18B	B1	90							
18C	B2	80							
18D	B2	90							

€ WALL AND

FOOTING

TYPICAL SECTION

RIGHT-OF-WAY

SEE CONTRACT

SOLID GROUT CAP

BOND BEAM AT TOP

2" (TYP.)

WALL HT	CMU WIDTH	х	V
6' - 0"	8"	_	2' -
8' - 0"	8"	_	2' -
10' - 0"	8"	_	2'
12' - 0"	8"	_	3' -
14' - 0"	8"	_	3' -
16' - 0"	10"	5' - 4"	3' -
401 011	400	01 011	

	TYPE 18A									
WALL HT	CMU WIDTH	x	w	BAR "A"	BAR "C"	BAR "D"	BAR "E"	WALL HT		
6' - 0"	8"	_	2' - 0"	3 ~ #4	_	#6 @ 48"	#4 @ 18"	6' - 0"		
8' - 0"	8"	_	2' - 3"	3 ~ #4	_	#6 @ 48"	#4 @ 18"	8' - 0"		
10' - 0"	8"	_	2' - 6"	3 ~ #4	_	#6 @ 48"	#4 @ 18"	10' - 0"		
12' - 0"	8"		3' - 0"	4 ~ #4		#6 @ 48"	#4 @ 18"	12' - 0"		
14' - 0"	8"		3' - 3"	4 ~ #4		#6 @ 36"	#4 @ 18"	14' - 0"		
16' - 0"	10"	5' - 4"	3' - 9"	5 ~ #4		#6 @ 16"	#4 @ 18"	16' - 0"		
18' - 0"	10"	6' - 0"	4' - 0"	5 ~ #4	#6 @ 48"	#6 @ 48"	#4 @ 18"	18' - 0"		
20' - 0"	10"	6' - 8"	5' - 0"	5 ~ #4	#6 @ 32"	#6 @ 32"	#4 @ 18"	20' - 0"		
22' - 0"	10"	7' - 4"	5' - 6"	5 ~ #4	#6 @ 24"	#6 @ 24"	#4 @ 18"	22' - 0"		
24' - 0"	10"	8' - 0"	6' - 3"	5 ~ #4	#6 @ 16"	#6 @ 16"	#4 @ 18"	24' - 0"		

W BAR "A"	BAR "C"	BAR "D"	BAR "E"	
' - 3" 3 ~ #4			BAR "E"	
0 0	_	#6 @ 48"	#4 @ 18"	
' - 9" 4 ~ #4		#6 @ 48"	#4 @ 18"	
' - 3" 4 ~ #4	_	#6 @ 48"	#4 @ 18"	
' - 9" 4 ~ #4	_	#6 @ 40"	#4 @ 18"	
' - 3" 5 ~ #4	#6 @ 40"	#6 @ 40"	#4 @ 18"	
' - 3" 5 ~ #4	#6 @ 32"	#6 @ 32"	#4 @ 18"	
' - 0" 6 ~ #4	#6 @ 24"	#6 @ 24"	#4 @ 18"	
' - 0" 5 ~ #4	#7 @ 24"	#7 @ 24"	#4 @ 18"	
' - 9" 5 ~ #4	#7 @ 16"	#7 @ 16"	#4 @ 12"	
' - 6" 5 ~ #4	#8 @ 16"	#8 @ 16"	#4 @ 12"	
TVDE 40D				
	1 - 9"	1 - 3" 4 ~ #4 2 - 9" 4 ~ #4 3" 5 ~ #4 #6 @ 40" 4 - 3" 5 ~ #4 #6 @ 32" 5 - 0" 6 ~ #4 #6 @ 24" 6 - 0" 5 ~ #4 #7 @ 24" 7 - 9" 5 ~ #4 #7 @ 16" 7 - 6" 5 ~ #4 #8 @ 16"	1 - 9" 4 ~ #4 — #6 @ 48" 2 - 3" 4 ~ #4 — #6 @ 48" 3" 4 ~ #4 — #6 @ 40" 4 - 3" 5 ~ #4 #6 @ 40" #6 @ 40" 5 - 3" 5 ~ #4 #6 @ 32" #6 @ 32" 6 - 0" 6 ~ #4 #6 @ 24" #6 @ 24" 7 - 0" 5 ~ #4 #7 @ 24" #7 @ 24" 8 - 9" 5 ~ #4 #7 @ 16" #7 @ 16"	

24' - 0"	10"	8' - 0"	6' - 3"	5 ~ #4	#6 @ 16"	#6 @ 16"	#4 @ 18"	24' - 0"	10"	12' - 0"	8' - 6"	5 ~ #4	#8 @ 16"	#8 @ 16"
	TYPE 18C							TYPE 18D						
WALL HT	CMU WIDTH	х	w	BAR "A"	BAR "C"	BAR "D"	BAR "E"	WALL HT	CMU WIDTH	x	w	BAR "A"	BAR "C"	BAR "D"
6' - 0"	8"	_	2' - 0"	3 ~ #4	_	#6 @ 48"	#4 @ 18"	6' - 0"	8"	_	2' - 6"	3 ~ #4	_	#6 @ 48"
8' - 0"	8"	_	2' - 6"	3 ~ #4	_	#6 @ 48"	#4 @ 18"	8' - 0"	8"	_	3' - 3"	5 ~ #4	_	#6 @ 48"
10' - 0"	8"	_	2' - 9"	3 ~ #4		#6 @ 48"	#4 @ 18"	10' - 0"	10"	4' - 0"	3' - 6"	5 ~ #4		#6 @ 24"
12' - 0"	8"	_	3' - 3"	3 ~ #4	_	#6 @ 40"	#4 @ 18"	12' - 0"	10"	4' - 0"	4' - 3"	5 ~ #4	#6 @ 48"	#6 @ 32"
14' - 0"	10"	4' - 0"	3' - 9"	5 ~ #4		#6 @ 16"	#4 @ 18"	14' - 0"	10"	4' - 8"	5' - 3"	5 ~ #4	#6 @ 32"	#6 @ 24"
16' - 0"	10"	4' - 8"	4' - 3"	5 ~ #4	#6 @ 40"	#6 @ 40"	#4 @ 18"	16' - 0"	10"	5' - 4"	6' - 3"	5 ~ #4	#6 @ 24"	#7 @ 16"
18' - 0"	10"	5' - 4"	5' - 0"	5 ~ #4	#6 @ 32"	#6 @ 32"	#4 @ 18"	18' - 0"	10"	7' - 4"	7' - 0"	5 ~ #4	#6 @ 16"	#7 @ 16"
20' - 0"	10"	6' - 0"	5' - 9"	5 ~ #4	#6 @ 24"	#6 @ 24"	#4 @ 18"	20' - 0"	10"	9' - 8"	8' - 0"	5 ~ #4	#7 @ 16"	#8 @ 16"
22' - 0"	10"	7' - 0"	6' - 6"	5 ~ #4	#6 @ 16"	#6 @ 16"	#4 @ 18"	22' - 0"	10"	12' - 0"	9' - 0"	5 ~ #4	#8 @ 16"	#8 @ 16"
24' - 0"	10"	8' - 0"	7' - 6"	5 ~ #4	#7 @ 16"	#7 @ 16"	#4 @ 12"	24' - 0"	10"	15' - 0"	9' - 9"	6 ~ #4	#9 @ 16"	#8 @ 16"

NOTES

BAR "E"

#4 @ 18"

#4 @ 18"

#4 @ 18"

#4 @ 18"

#4 @ 18"

#4 @ 18"


#4 @ 18"

#4 @ 12"

#4 @ 12"

#4 @ 12"

- 1. Wall to be designated Noise Barrier Wall Type 18A, 18B, 18C or 18D. The Contract specifies actual wall designations.
- 2. For intermediate wall heights, use the next higher H.
- 3. All masonry shall be hollow unit and installed as running bond.
- 4. All masonry is to be specially inspected.
- 5. All Concrete Masonry Unit (CMU) cells that have vertical steel reinforcing bars or bond beam units shall be filled with grout.
- 6. Panels shall have at least 3 feet of level ground on each side.
- Construction joints in the footing shall be spaced at 120 feet maximum.
- See "Masonry Wall Finishes and Details" sheets for masonry block finishes, special shapes, sizes and layout.



MASONRY WALL ON OFFSET SPREAD FOOTING



NOISE BARRIER WALL TYPE 18


STANDARD PLAN D-2.64-00

SHEET 1 OF 2 SHEETS


APPROVED FOR PUBLICATION

11-10-05 Harold J. Peterfeso


NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE.
THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE
AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A COPY MAY BE OBTAINED UPON REQUEST.




TYPICAL EXPANSION JOINT



EXPANSION JOINT AT WIDTH STEP






DETAIL (A)

TYPICAL BOTH SIDES OF WALL

BOND BEAM DETAIL



MASONRY WALL ON OFFSET SPREAD FOOTING




NOISE BARRIER WALL TYPE 18

STANDARD PLAN D-2.64-00

SHEET 2 OF 2 SHEETS

APPROVED FOR PUBLICATION

Harold J. Peterfeso 11-10-05



FOOTING WIDTH TRANSITION DETAIL

(FOR LOCATIONS WITHOUT FOOTING STEP) NOTE: TRANSVERSE BARS NOT SHOWN

> NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A COPY MAY BE OBTAINED UPON REQUEST.